

## **IN THE CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the application. An identifier indicating the status of each claim is provided.

### **Listing of Claims**

1. (Currently Amended) An image processing device comprising:

process generation means for generating processes for performing image processing that handles image data and sequentially outputting process data containing instructions required to execute each of the processes;

a plurality of series-connected execution means each of which executes a process related to the process data, wherein the process data contains an address of the execution means for executing the process related to the process data,

wherein the plurality of series-connected execution means are divided into a plurality of suites, each of the plurality of suites including a predetermined number of the series-connected execution means; and

for each suite of a predetermined number of the consecutive execution means, a plurality of route selection means for selecting any one of the input side and an output side of each of the suites to supply the input process data, each of the plurality of route selection means being inserted to an input side of each of the plurality of suites, respectively;

wherein each of the plurality of route selection means comprises:

first address storage means for storing an address of each of the plurality of execution means that make up the immediately following suite;

first address decision means for outputs a decision signal that indicates a first state if at least one of addresses stored in the first address storage means is present among the addresses of the execution means that are contained in the input process data; and

first switching means for supplying, depending on the decision signal output from the first address decision means, the input process data to the input side of the immediately following one of the suites if the decision signal indicates the first state and, otherwise, to the output side of this immediately following one of the suites.

2. (Previously Presented) The image processing device according to claim 1, wherein each of the plurality of execution means comprises:

processing means for performing processing of image data in accordance with each of the instructions contained in the input process data, altering the input process data to obtain process data to be output based on a result of the processing, and outputting a request signal that becomes a second state when the process data to be output is output;

second address storage means for storing an address of itself;

second address decision means for outputting a decision signal that indicates a the first state if the address of itself stored in the second address storage means is present among the addresses of the execution means contained in the input process data; and

second switching means for outputting, depending on the decision signal output from the second address decision means and the request signal output from the processing means, the process data to be output obtained by the processing means as output process data if

the request signal is the second state and the input process data as the output process data if the request signal is not the second state and the decision signal is not the first state.

3. (Original) The image processing device according to claim 2, wherein each of the plurality of execution means further comprises data storage means for storing image data; and

wherein the processing means performs as the image data processing any one of writing of image data to the data storage means, reading of the image data from the data storage means, and calculation of a difference on the image data.

4. (Previously Presented) The image processing device according to claim 2, wherein the second switching means outputs any one of high-level data and low-level data if the request signal is not the second state and the decision signal is the first state.

5. (Original) The image processing device according to claim 1, wherein the image processing includes detection of a motion vector.

6. (Previously Presented) An image processing device comprising:  
process generation means for generating processes for performing image processing that handles image data and sequentially outputting process data containing instructions required to execute each of the processes; and

a plurality of series-connected execution means each of which executes a process related to the process data wherein the process data contains an address of the execution means for executing the process related to the process data,

wherein each of the plurality of execution means comprises:

processing means for performing processing of image data in accordance with the instructions contained in the input process data, altering the input process data to obtain process data to be output based on a result of the processing, and outputting a request signal that indicates a second state when the process data to be output is output;

address storage means for storing an address of itself;

address decision means for outputting a decision signal that indicates a first state if the address of itself stored in the address storage means is present among the addresses of the execution means contained in the input process data; and

switching means for outputting, depending on the decision signal output from the address decision means and the request signal output from the processing means, the process data to be output obtained by the processing means as output process data if the request signal is the second state, and the input process data as the output process data if the request signal is not the second state and the decision signal is not the first state.

7. (Original) The image processing device according to claim 6,

wherein each of the plurality of execution means further comprises data storage means for storing image data; and

wherein the processing means performs as the image data processing any one of writing of image data to the data storage means, reading of the image data from the data storage means, and calculation of a difference on the image data.

8. (Previously Presented) The image processing device according to claim 6, wherein the switching means outputs any one of high-level data and low-level data if the request signal is not the second state and the decision signal is the first state.

9. (Original) The image processing device according to claim 6, wherein the image processing includes detection of a motion vector.

*THE REMAINDER OF THIS PAGE INTENTIONALLY LEFT BLANK*